

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number  
**WO 2004/018901 A1**

(51) International Patent Classification<sup>7</sup>: **F16H 25/20**

(21) International Application Number:  
PCT/DK2003/000551

(22) International Filing Date: 20 August 2003 (20.08.2003)

(25) Filing Language: Danish

(26) Publication Language: English

(30) Priority Data:  
PA 2002 01229 20 August 2002 (20.08.2002) DK

(71) Applicant (for all designated States except US): LINAK A/S [DK/DK]; Smedevænget 8, Guderup, DK-6430 Nordborg (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ABRAHAMSEN, John [DK/DK]; Strelbergvej 14, Østerholm, DK-6430 Nordborg (DK).

(74) Common Representative: LINAK A/S; Smedevænget 8, Guderup, DK-6430 Nordborg (DK).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A LINEAR ACTUATOR



(57) Abstract: A linear actuator, preferably for sickbeds and beds for domestic use, comprises a reversible electric motor (2) which, via a reduction gear, drives a spindle (4) with a nut (5) secured against rotation so that an activating element (6) connected with the nut is moved to and fro in response to the direction of rotation of the motor. In an emergency, the actuator may be driven manually with a hand crank, as a rear attachment, with which the actuator is secured, has a longitudinal opening in the longitudinal axis of the spindle, whereby the hand crank may be caused to engage the spindle. For this purpose, a shaft member is mounted in the rear attachment, said shaft member being engaged with the spindle and protruding rearwards from the rear attachment with one end. Control of the motor typically takes place via an H-bridge so that the motor does not short-circuit when the actuator is operated manually, it is ensured that the motor is not self-locking when the actuator is operated manually.

### A linear actuator

The present invention relates to a linear actuator comprising a cabinet, a reversible electric motor with a motor shaft, a reduction gear operatively  
5 connected with the motor shaft, a spindle operatively connected with the reduction gear, a spindle nut secured against rotation on the spindle, an activating element connected with the spindle nut and for attachment to the structure in which the actuator is to be incorporated, a rear attachment dis-  
posed in extension of the spindle opposite the activating element likewise  
10 for attachment of the actuator in the structure in which the actuator is to be incorporated.

State of the art actuators are known e.g. from EP 531 247 A1, EP 586 326 A1, EP 647 799 and EP 662 573 A1 as well as WO 98/30816, all to Linak  
15 A/S. These actuators are used inter alia for incorporation in hospital beds and sickbeds. For an example of a hospital bed, reference may be made to EP 488 552 A1 to Huntleigh Technology plc. For hospital beds, the power supply is typically based on a transformer and a rectifier supplemented with a rechargeable battery pack, so that the bed may also be operated even  
20 though it is not connected to the mains, e.g. when it is driven from one location to another or during a temporary stay e.g. in an examination room or X-ray room. In emergency situations where the bed must be capable of quickly assuming a specific position, e.g. Trendelenburg's position, the actuators for hospital beds are provided with a disengagement device, where  
25 the spindle is disengaged from gear and motor so that e.g. the back and leg sections seek toward the horizontal by their own weight. The adjustment is then made manually by grasping the section and placing it in the desired position. The disengagement device may also be used in the event that the battery pack should fail, or another defect should occur. Where sickbeds  
30 and beds for domestic use are involved, equipment such as battery pack and disengagement device adds considerably to the costs. Instead of the

rechargeable battery pack, an ordinary small 9V battery may be used, with the drawbacks this entails, and, moreover, it is frequently arranged at a location which is difficult to reach.

- 5 In bed structures having integrated spindles for adjustment of the bed, cf. e.g. US 5 269 031 to Alexander, it is known to use a hand crank for manual adjustment of the bed in case of power failure, or altogether carry out the adjustment with a hand crank.
- 10 US 2 541 529 to McVicker discloses a single example of an actuator where, under normal conditions, the spindle is driven by an electric motor via a worm gear, which, in emergency situations, can be driven by a hand crank, as the worm wheel is disengaged from the worm. The worm wheel is connected with the spindle via a specially configured, longitudinally slidable,
- 15 spring-loaded coupling member. For introduction of the hand crank, a cap must first be screwed off, and then the hand crank is introduced and a cap with a bearing, mounted on the hand crank, is screwed on. The structure is bulky, as it requires a great mounting length as well as a large diameter, since the end of the hand crank must be capable of being introduced
- 20 therein. In addition, the actuator has to be secured in another manner than by a rear attachment, as it must be possible to screw the caps off and on.

The object of the invention is to provide a state of the art actuator which may be operated manually by a hand crank without intervention in its basic

25 structure, and which is additionally constructionally simple and inexpensive to manufacture.

This is achieved according to the invention by constructing the actuator such that its rear attachment has a longitudinal opening in the longitudinal

30 axis of the spindle, so that the hand crank may be engaged with the spindle via this opening. The structure is simple and inexpensive and does not in-

terfere with the basic configuration of the actuator.

5 As stated in claim 2, a shaft member is provided in the opening, said shaft member being connected at its one end with one end of the spindle and configured at its other end for operative reception of the end of the hand crank, it being desired to avoid introducing the end of a hand crank deep into the interior of the actuator.

10 In the embodiment defined in claim 3, the shaft member is formed by an extension of the spindle, which then preferably protrudes from the end of the rear attachment.

15 As stated in claim 4, the shaft member is a separate element mounted in the rear attachment. This is easier in terms of mounting, since the rear attachment may then be made as a unit with integrated shaft member. It also provides the option of preparing the actuator for optional mounting of rear attachment with or without a facility for manual operation.

20 As stated in claim 5, the shaft member may be secured to the end of the spindle with a cylindrical object, and, according to claim 6, the connection is particularly simple in that the cylindrical object has an end bottom with a hole at the end of the spindle, and that this is shaped as a rivet head for retaining the cylindrical object. As stated in claim 7, the shaft member may be connected with the cylindrical object in a simple manner by a pin.

25

The opening may have various geometrical cross-sections, but a circular cross-section and a shaft member likewise of circular cross-section have evident advantages in terms of mounting and sealing.

30 Where the rear attachment is a separate object mounted at the end of the cabinet, the actuator may be made impervious to moisture and water by a

seal between the rear attachment and the cabinet as well as one between the shaft member and the opening, as stated in claim 9. Where the rear attachment is split about a longitudinal central plane, the two seals, as stated in claim 10, may be formed as two integrated halves and be applied to the rear attachment, which facilitates the application and the correct positioning of the seals.

As stated in claims 11 and 12, an H-bridge in the electrical control of the actuator comprises at least a diode so that the motor is not short-circuited when the actuator is operated manually with the hand crank. It is hereby easy to operate the actuator manually, since it is not necessary to overcome the self-locking ability of the motor because of short-circuiting of it. The drawback is then that the motor no longer contributes to the self-locking ability of the actuator, but this may be compensated for in another manner, if necessary, e.g. spindles with a greater self-locking ability or brakes. Another drawback is also that the energy, which is otherwise dissipated in the motor by short-circuiting of it, now has to be dissipated in another manner. This, however, has been found to have a positive influence on the deceleration that becomes softer, which is felt more comfortable by the user. Previously, there have been extra means for overcoming a too hard deceleration. The structure has also been found to have a favourable influence on the service life of the relays of the H-bridge, which can otherwise be a problem. As a result of the diode, the relay is not left energized when it is switched off, in contrast to a short-circuit of the motor where this acts as a generator and applies a very high voltage to the contact points of the relay.

An embodiment of the invention will be described more fully below with reference to the accompanying drawing, in which:

Fig. 1 is a longitudinal section through the actuator,

fig. 2 is an exploded view of a rear attachment with shaft member and seal,

fig. 3 is a perspective close-up of a seal, and

5

fig. 4 is a diagram of an H-bridge for the electrical control of the motor of the actuator.

10 As will appear from the drawing, the main components of the actuator are a cabinet 1, a reversible electric motor 2, typically a 24V or 48V DC motor, a worm gear with a worm wheel 3, a spindle 4, a spindle nut 5, an activating element 6, also called the inner pipe, an outer pipe 7 and a rear attachment 8. The actuator is generally constructed as described in the applicant's international application WO 02/29284, which is hereby incorporated by reference.

15

The worm wheel 3 is secured on the rear end of the spindle 4 and is in engagement with a worm configured as an extended part of the motor shaft. The worm wheel 3 is provided with a cylindrical element 10 on one side, on which a screw spring 11 is seated for increasing the self-locking ability of the spindle, as described more fully in EP 662 573 B1. One end of the screw spring is bent radially outwards and is secured in a metal insert. Next is a ball bearing 12 on a metal insert 13 with a part which is accommodated in a hollow in the cylindrical element 11 of the worm wheel, which are connected with each other by a splined connection.

20  
25

The ball bearing 12 is mounted in a recess in the rear attachment 8 consisting of two halves. The rear attachment 8 has an eye 14 at each side for attachment of the actuator in the structure in which it is to be incorporated.

30

The activating rod 6 is formed by a pipe and is secured with its rear end to

the spindle nut 5. The outer end of the rod is closed by a tightly fitting plastics plug. The rod is secured by means of an eye 15 to the structure in which the actuator is to be incorporated. The eye has a bearing face provided in that its hole rim is turned up into the hollow of the rod.

5

The outer pipe 7 is formed by an extruded aluminium pipe of non-circular cross-section. The outer end of the pipe accommodates an end cover 16 having a circular hole as a guide for the activating rod 6. The outer pipe is received with its rear end as a snug fit in a portion at the front end of a bracket secured to the motor housing, for further detail see WO 02/29284.

10

The outer pipe 7 internally has grooves for retaining the spindle nut 5 against rotation, said nut having corresponding external bosses on a collar which engage the grooves. The pipe additionally has two grooves opposite each other for insertion of a strip-shaped printed circuit board 17 carrying, at each end, an end stop contact 18, 19 which is activated by a spring arm mounted on a bracket in connection with the contact. When the spindle nut 5 reaches an end position, it will press the spring arm against the contact, which is then activated and stops the motor via the control.

15

20

In case of power failure, the actuator may be operated by a hand crank at the rear attachment 8 of the actuator. The end of the spindle has secured thereto a cylindrical object 20 with an end bottom, which is formed with a hole for the end of the spindle which is configured into a rivet head 21. The cylindrical object has such a large diameter that it retains the bearing 12 on the spindle. The rear attachment 8 accommodates two slide bearings 22, 23 for a shaft member 24, whose one end is passed into the cylindrical object and secured to it by a cotter pin 25 through aligned holes in the pipe object 20 and the shaft member 24. At the other end of the shaft member 24, a through cotter pin 26 is secured in a hole for cooperation with a slot in the hand crank.

25

30

Fig. 2 of the drawing shows an exploded view of the rear attachment which consists of two halves 14a, 14b, and also the shaft member 24 is shown together with two seal halves 31a, 31b, of which a larger picture of the lower seal half is shown in fig. 3. The slide bearing 22 also acts as a seal and is moved slightly outside the side wall for noise damping of the pin 32. The seal 22 is connected by the structure 33 with the seal 34 which is disposed in the groove 35 on the outer side of the rear attachment and seals against the cabinet. The structure 33 is received in a recess 36 in the joint face on the rear attachment. One side of the structure 33 has a side wall 33a which, in the recess 36, extends down on the outer side of the overlying structure, it being noted that the two seal halves are identical. This provides a good and safe seal of the shaft member as well as of the rear attachment as a whole. The seal is moreover easy to mount.

The control of the electric motor is based on an H-bridge which, as shown in fig. 4, comprises two relays 27, 28 for switching off the power to the motor and for reversing the direction of the current for reversing the direction of rotation of the motor. The relays are controlled via a manual control or by a control panel as well as by the end stop contacts 18, 19. Two diodes 29, 30 are inserted into the H-bridge which block the countervoltage generated in the electric motor when the power to the motor is switched off. Thus, the motor does not contribute to the self-locking ability of the actuator, and it is hereby easier to operate the actuator manually with the hand crank. The embodiment with the diodes additionally has the advantages mentioned in the preamble.

When the hand crank is operated, the spindle 4 is rotated, thereby displacing the spindle nut 5 and the activating rod 6 connected with it, as if the actuator were driven by the motor. It is noted that the worm wheel 3 is rotated by the spindle 4 and causes the motor to rotate via the worm.



The invention thus provides a compact actuator which may be operated by a hand crank, and which also provides additional advantages in usual operation, such as soft deceleration and longer service life of the relays in the H-bridge. In the present context, hand cranks are taken to mean mechanical hand cranks as well as battery-driven devices having an adapter for insertion over the end of the shaft member 24.

**PATENT CLAIMS**

1. A linear actuator comprising a cabinet (1), a reversible electric motor (2) with a motor shaft, a reduction gear operatively connected with the motor shaft, a spindle (4) operatively connected with the reduction gear, a spindle nut (5) secured against rotation on the spindle, an activating element (6) connected with the spindle nut (5) and for attachment to the structure in which the actuator is to be incorporated, a rear attachment (8) disposed in extension of the spindle opposite the activating element likewise for attachment of the actuator in the structure in which the actuator is to be incorporated, characterized in that the rear attachment (8) has a longitudinal opening in the longitudinal axis of the spindle, and that a hand crank may be engaged with the spindle via this opening for manual operation of the actuator.
2. An actuator according to claim 1, characterized in that a shaft member (24) is provided in the opening, said shaft member being connected at its one end with one end of the spindle (4) and configured at its other end for operative reception of the end of the hand crank.
3. An actuator according claim 2, characterized in that the shaft member (24) is formed by an extension of the spindle.
4. An actuator according to claim 2 or 3, characterized in that the shaft member (24) is a separate element mounted in the rear attachment (8).
5. An actuator according to claim 4, characterized in that the shaft member (24) is secured to the end of the spindle with a cylindrical object (20).
6. An actuator according to claim 5, characterized in that the cylin-

drical object (20) has an end bottom with a hole at the end of the spindle, and that this is shaped as a rivet head (21) for retaining the cylindrical object (20).

5 7. An actuator according to claim 6, characterized in that the shaft member (24) is connected with the cylindrical object (20) by a pin.

8. An actuator according to claim 1, characterized in that the opening has a circular cross-section, and that the shaft member (24) likewise has a circular cross-section.  
10

9. An actuator according to claim 1, characterized in that the rear attachment (8) is a separate member mounted at the end of the cabinet (1) with a seal, and that the shaft member (24) is likewise provided with a seal  
15 in the opening.

10. An actuator according to claim 9, characterized in that the rear attachment (8) is split about a longitudinal central plane, and that the two seals are formed as two integrated halves.  
20

11. An actuator according to claim 1, characterized in that it comprises a power supply with a connection to the mains voltage and an outlet with a reduced voltage for connection to the motor of the actuator, an electrical control comprising an H-bridge with two relays (27, 28) for switching  
25 the power to the motor on and off and for reversing the direction of the current for reversing the direction of rotation of the motor, and that the H-bridge comprises at least a diode (29, 30) so that the motor is not short-circuited when the actuator is operated manually with the hand crank.

30 12. An actuator according to claim 11, characterized in that the H-bridge comprises a further diode (30, 29) so that the motor is not short-cir-

cuitied when the actuator is operated manually with the hand crank for running toward another end position.




Fig. 1




Fig. 2




Fig. 2





Fig. 3

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 03/00551

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F16H 25/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F16H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2541529 A (G.D. MCVICKER), 13 February 1951 (13.02.51)	1,8
A	--	2-7;9-12
A	US 5269031 A (ALEXANDER), 14 December 1993 (14.12.93)	1-12
A	EP 0911542 A2 (ABB SACE SPA), 28 April 1999 (28.04.99)	1-12
A	WO 9830816 A1 (LINAK A/S), 16 July 1998 (16.07.98)	1-12
	-----	

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

4 November 2003

Date of mailing of the international search report

05-11-2003

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Per-Olof Warnbo / JA A  
Telephone No. +46 8 782 25 00

# INTERNATIONAL SEARCH REPORT

Information on patent family members

06/09/03

International application No.

PCT/DK 03/00551

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	2541529	A	13/02/51	NONE	
US	5269031	A	14/12/93	CA US	2042768 A,C 5095562 A
EP	0911542	A2	28/04/99	DE IT	69808014 D,T 1295374 B
WO	9830816	A1	16/07/98	AT AU DE DK DK EP SE JP US	233872 T 5311898 A 69719543 D 151096 A 944788 T 0944788 A,B 0944788 T3 2001507110 T 6158295 A
					15/03/03 03/08/98 00/00/00 17/07/98 30/06/03 29/09/99 29/05/01 12/12/00